



GB Chain No.	Pitch	Chain Width	Pin diameter	Pin length		Distance from hole centre to tooth	Plate Depth	Guide form	Number of plates	Ultimate tensile strength	Weight per meter
	P	B min	d2 max	L max	Lc max	h1	h2max		N	Q min	q
	mm	mm	mm	mm	mm	mm	mm		kN/lbf	kg/m	
CL06-13.5		13.5		18.5	20.0			Outside	9	10.0	0.6
CL06-16.5		16.5		21	23.0			Outside	11	12.5	0.73
CL06-19.5	9.525	19.5	3.28	24.5	26.0	5.3	10.0	Outside	13	15.0	0.85
CL06-22.5		22.5		27.5	29.0			Outside	15	17.52	1
CL06-28.5		28.5		33.5	35.0			Outside	19	22.5	1.26
CL08-19.5		19.5		24.5	26.0			Outside	13	23.4	1.15
CL08-22.5		22.5		27.5	29.0			Outside	15	27.4	1.33
CL08-25.5		25.5		30.5	32.0			Outside	17	31.3	1.5
CL08-28.5	12.700	28.5	5.08	33.5	35.0	7.0	13.4	Inside	19	35.2	1.68
CL08-34.5		34.5		39.5	41.0			Inside	23	43.0	2.04
CL08-40.5		40.5		45.5	47.0			Inside	27	50.8	2.39
CL08-46.5		46.5		51.5	53.0			Inside	31	58.6	2.74
CL08-52.5		52.5		57.5	59.0			Inside	35	66.4	3.1
CL10-30.0		30.0		37.0	38.2			Inside	15	45.6	2.21
CL10-38.0		38.0		45.0	46.2			Inside	19	58.6	2.8
CL10-46.0	15.875	46.0	5.92	53.0	54.2	8.7	16.7	Inside	23	71.7	3.39
CL10-54.0		54.0		61.0	62.4			Inside	27	84.7	3.99
CL10-62.0		62.0		69.0	70.4			Inside	31	97.7	4.58
CL12-38.0		38.0		45.0	46.5			Inside	19	70.0	3.37
CL12-46.0		46.0		53.0	55.5			Inside	23	86.0	4.08
CL12-54.0	19.050	54.0	6.90	61.0	62.8	10.50	20.0	Inside	27	102.0	4.78
CL12-62.0		62.0		69.0	70.8			Inside	31	117.0	5.5
CL12-70.0		70.0		77.0	78.8			Inside	35	133.0	6.2
CL16-45.0		45.0		52.0	53.5			Inside	15	111.0	5.31
CL16-51.0		51.0		58.0	59.5			Inside	17	125.0	6.02
CL16-57.0	25.400	57.0	8.9	64.0	65.5	14.0	26.70	Inside	19	141.0	6.37
CL16-69.0		69.0		76.2	77.7			Inside	23	172.0	8.15
CL16-81.0		81.0		68.2	89.7			Inside	27	203.0	9.57
CL16-93.0		93.0		100.2	101.7			Inside	31	235.0	10.98
CL20-57.0		57.0		66.6	69.6			Inside	19	165.0	8.42
CL20-69.0		69.0		78.6	81.6			Inside	23	201.0	10.19
CL20-81.0	31.750	81.0	10.84	90.6	93.6	17.5	33.40	Inside	27	237.0	11.96
CL20-93.0		93.0		102.6	105.6			Inside	31	273.0	13.73
CL20-105.5		105.5		114.6	117.65			Inside	35	310.0	15.5
CL20-117.0		117.0		126.6	129.6			Inside	39	346.0	17.27
CL20-117.0		117.0		129.0	131.0			Inside	39	415.0	20.73
CL24-129.0	38.10	129.0	12.8	141.0	143.0	20.96	40.01	Inside	43	458.0	22.86
CL24-141.0		141.0		153.0	155.0			Inside	47	502.0	24.99