



CATERPILLAR SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
CAT 307C	240-8361	810	568	82	62	62	29	38	75
CAT 312CL	229-1077	1093	883	72.5	50	62	34-φ18	38-M16	90
CAT 311	231-6853	1115	883	75	60	67	29-φ18	30-M16	90
CAT 312B	616411	1115	883	75	60	67	29-φ18	30-M16	90
CAT 312CL	229-1077	1093	883	72.5	50	62	34-φ18	38-M16	90
CAT 312C	229-1077	1093	883	72.5	50	62	34-φ18	38-M16	90
CAT 315	148-4568	1205	961	94	74	84	34	30	98
CAT 318B	148-4568	1205	961	94	74	84	34	30	98
CAT 315C	229-1080	1205	961	94	74	84	34-φ22	36-M20	98
CAT 319C	227-6079	1310	1065	106	84	88	36	36/M20	90
CAT320B	1141414	1314	1084	100	85	87	33-Φ22	36-M20	110
CAT320BL	121-8222	1314	1084	100	85	87	33-Φ22	36-M20	110
CAT 320	7Y1565	1314	1084	100	85	87	33-φ22	36-M20	110
CAT 320B	114-1505	1314	1084	100	85	87	33-Φ22	36-M20	110
CAT 320BL	177-7723	1314	1084	100	85	87	33-Φ22	36-M20	110
CAT 320C	227-6081	1316	1081	105	73	93	42-φ22	40-M20	110
CAT 320C	227-6147	1316	1081	105	73	93	42-φ22	40-M20	110
CAT 320C	171-9425	1316	1081	105	73	93	42-φ22	40-M20	110
CAT 320D	227-6082	1316	1081	105	73	93	42-φ22	40-M20	110
CAT 320L	7Y1563	1316	1084	105	85	92	38-φ22	36-M20	110
CAT 320L	7Y1563	1318	1084	105	86	90	38-φ22	36-M20	110
CAT 225	8K4127	1451	1038	105	92	90	29-φ24	36-φ24	104
CAT 322C	221-6764	1460	1163	110	88	95	34-Φ26	36-M24	85
CAT 324D	227-6085	1460	1164	110	88	95	34-Φ26	36-M24	85
CAT 325	7Y0745	1495	1164	110	93	95	35	38	85
CAT 325C	227-6087	1495	1164	110	93	95	38-φ26	42	85
CAT 326	353-0649	1462	1164	110	89	95	34-φ26	36-M24	85
CAT 329D	227-6087	1495	1164	110	93	95	38-Φ26	42-M24	85
CAT 330	7Y0933	1664	1313.5	140	100	124	42-φ26	46-M24	84
CAT 330	1994559	1664	1313.5	141	100	124	42-φ26	46-M24	84
CAT 330	353-0487	1664	1313.5	140	100	124	46-φ26	46-M24	84
CAT 336D	353-0489	1665	1313	140	100	122	42	46	84
CAT 336DL	227-6089	1665	1314	140	100	125	42	46	84
CAT 336DL	353-0680	1664	1313.5	139	100	124	46-φ26	46-M24	84
CAT 336D	353-0490	1665	1313	140	100	122	42	46	84
CAT 345	227-6052	1680	1318	140	107	126	54-φ26	70-M24	96
CAT 345B	136-2969	1680	1343	140	107	126	45-Φ26	60-M24	136
CAT 345BII	227-6094	1680	1318	140	108	125	54-Φ26	70-M24	96
CAT 345BL	169-5536/169-5537	1680	1343	140	107	125	45-Φ26	60-M24	136
CAT 345DL	227-6037	1680	1318	140	107	125	54-Φ26	70-M24	96
CAT 349D	353-0490	1666	1315	140	100	123	46	46	84
CAT 350	1026392	1680	1343	140	107	126	45-φ26	60-M24	136

CAT 365C	199-4565	1810	1348	180	140	152	37	60	98
CAT 365C	227-6096	1805	1348	180	138	150	37	60	98
CAT 365C	227-6097	1805	1348	180	138	150	37	60	98
CAT 365CL	397-9666	1805	1348	180	138	150	37	60	98
CAT374F	378-9586	1820	1348	180	140	150	37	60	98
CAT374	333-3009	1820	1348	180	136	150	37	60	98
CAT374	367-8361	1820	1348	180	136	150	37	60	98
CAT 385C	199-4491	1820	1348	180	146	150	37	60	98
CAT 385C	227-6099	1820	1348	180	146	150	37	60	98
CAT 385BL	227-6098	1820	1348	180	138	150	37	60	98
CAT 385CL	227-6099	1950	1456	217	170	180	48	74	93
CAT 140	2436650	1113	871	96	75	85	31	30	89

CASE SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
CX130	KNB10130	1172	972	88	65	78	28	36	98
CX130	KNB 11840	1172	973	88	65	78	28	36	98
CX210	KRB1347	1330	1094	103	74	92	31	36	92
CX210	KRB1603	1330	1094	103	74	92	31	36	92
CX210	KRB10160	1330	1093	102	74	92	31-φ22	36-M20	92
CX210B	KRB10160	1330	1093	102	74	92	31-φ22	36-M20	92
CX210	KRB10180	1330	1093	102	74	92	31-φ22.5	36-M20	92
CX210B	KRB11710	1330	1093	102	74	92	31-φ22	36-M20	92
CX210C	KRB11710	1330	1093	102	74	92	31-φ22	36-M20	92
CNH E215	72203516	1312	1082	110	79	98	33	36	110
CNH E215	87472588	1312	1082	110	79	98	33	36	110
CX240	KBB0878	1375	1094	124	88	114	27-Φ26	36-M24	92
CX240	KBB0282	1375	1094	124	80	114	26-φ26	36-M24	92
CX240	KBB 10080	1376	1093	125	88	114	27	36	92
CX240B	KBB11350	1377	1094	124	88	114	28-26	36-M24	92
CX460	KTB10010	1615	1275	145	125	135	41-Φ26	46-M24	92
CX290	KBB10100	1615	1274	122	100	110	41	46	92

DAEWOO SLEWING BEARING

No	Model	External diameter	Internal diameter	Total height	Outer ring height	Inner ring height	Outer ring hole	Inner ring hole	Tooth Number
1	DH55-5（V）	811	617	75	65	65	24-φ17.5 e	24-φ17.5 e	90
2	DH60	811	617	75	65	65	24-φ17.5 e	24-φ17.5 e	90
3	DH80GO	901	640	82	72	65	24-φ20 e	24-M18 e	82
4	DH80-7	901	640	82	72	65	24-φ20 e	24-M18 e	82
5	DH150-5	1202	947	83	75	70	36-φ22 e	36-M20 e	80
6	DH150-7	1202	947	83	75	70	36-φ22 e	36-M20 e	80
7	DH220-2	1310	1084	110	80	95	36-φ21.5 e	36-M20*1.5 e	79
8	DH220-3	1310	1084	110	80	95	36-φ21.5 e	36-M20*1.5 e	79
9	DH215-7	1327	1084	112	90	95	36-φ21.5 e	36-M20*1.5 e	92
10	DH220-5	1327	1084	112	90	95	36-φ21.5 e	36-M20*1.5 e	92
11	DH220-7	1327	1084	112	90	95	36-φ21.5 e	36-M20*1.5 e	92
12	DH225LC-7	1327	1084	112	90	95	36-φ21.5 une	36-M20*1.5 e	92
13	DH225LC-9	1327	1084	112	90	95	36-φ21.5 une	36-M20*1.5 e	92
14	DX225LC	1327	1084	112	90	95	36-φ21.5 une	36-M20*1.5 e	92
15	DH258-7(82Z)	1410	1131	117	89	105	35-φ25 une	36-M24*2 e	82
16	DH300LC-7	1475	1165	120	90	110	35-φ25 une	36-M24 e	85
17	DH300-5（V）	1461	1162	120	95	105	35-φ25 e	36-M24*2 e	85
18	DH280	1461	1162	120	95	105	35-φ25 e	36-M24*2 e	85
19	DH290-5	1461	1162	120	95	105	35-φ25 e	36-M24*2 e	85
20	DX300	1475	1165	120	90	110	35-φ25 une	36-M24 e	85
21	DH340	1543	1235	132	103	120	35-φ25 une	40-M24 e	90
22	DH360-5	1543	1235	132	103	120	35-φ25 une	40-M24 e	90
23	DH370LC-7	1552	1236	132	103	120	35-φ25 une	40-M24 e	90

24	DH370LC-9	1552	1236	132	103	120	35-φ25 une	40-M24 e	90
25	DH420LC-7	1552	1236	132	103	120	35-φ25 une	40-M24 e	90
26	DH500-7	1682	1319	138	119	110	44-φ25 une	44-φ25 e	111

KOMATSU SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total Height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
PC75UU-2	201-25-61100	806	594	74	59	61	24-φ18	24-φ18	76
PC100-6	203-25-62100	1105.5	883.5	75	65	65	34-φ18	38-M16	90
PC110R	206-25-11100	1106	884	75	65	64	34-φ18	36-M16	90
PC120-6	203-25-62100	1105.5	883.5	75	65	65	34-φ18	38-M16	90
PC130-7	SAA4D95L	1106	884	75	65	64	34-Φ18	38-M16	110
PC150LCK-6	21P-25-K1100	1188	923	83	73	67	26-Φ22	30-Φ22	94
PC160-6K	21P-25-K1100	1188	923	83	73	67	26-Φ22	30-Φ22	94
PC160-7	21K-25-00101	1224	973	82	67	74	32-φ24	36-M20	99
PC200	205-25-00015	1242	916	100	90	90	22	36	78
PC210NIC-7K	20Y-25-00301	1323	1074	112	78	102	33-Φ24	36-M22	92
PC200-5	20Y-25-11103	1303	1083.5	109	86	90	26-M24	36-M20	110
PC200-8	206-25-00200	1321	1077	100	77	90	32-Φ24	36-M20	96
PC200-6	20Y-25-20200	1322	1083	100	77	90	32-Φ24	36-M20	110
PC200-6Z	20Y-25-22200	1322	1083.5	99	76	90	32-φ24	36-M20	110
PC200-6	S6D102-1	1323	1083	100	77	90	32-Φ26	32-M20	92
PC200-7	20Y-25-21200	1322	1083.5	99	76	90	32-φ24	36-M20	110
PC220-7	120Y-25-21300	1322	1082	100	76	90	32-φ24	36-M20	110
PC200LC-7	20Y-25-21200	1323	1083	100	77	90	32-Φ26	36-M20	110
PC220	205-25-00022	1302	1083	104	82	90	26	36	110
PC220LC-6LE	20Y-25-A1101	1322	1082	100	76	90	32-Φ26	36-M22	110
PC220-6	20Y-25-21200	1323	1083	100	77	90	32-Φ26	36-M20	110
PC220-6	20Y-25-21100	1323	1083	100	77	90	32-Φ26	36-M20	110
PC220-7	206-25-00301	1323	1074	112	78	102	32-Φ24	36-M22	92
PC220-8	206-25-00320	1321	1077	100	77	90	32-φ24	36-M20	96
PC220LC-8	206-25-00301	1323	1072	112	77	102	32-Φ24	36-M22	92
PC228US-3	22U-25-00201	1322	1082	100	76	90	32-Φ26	36-M20	110
PC228	22U-25-00210	1322	1082	100	76	90	32-Φ26	36-M20	110
PC228	22U-25-00220	1322	1082	100	76	90	32-Φ26	36-M20	110
PC240-3	205-25-00023	1303	1084	104	83	90	26	36	110
PC240-7	206-25-00301	1323	1072	112	77	102	32	36	92
PC300-6	207-25-61100	1532	1235	125	95	113	35-φ26	40-M24	90
PC300-7	207-25-61100	1532	1235	125	95	113	35-φ26	40-M24	90
PC300-7	207-25-61700	1532	1235	125	95	113	35-φ26	40-M24	90
PC300LC-5	207-25-51100	1532	1235	125	95	113	35-M24	40-M24	90
PC300LC-6	207-25-61100	1532	1235	125	95	113	35-φ26	40-M24	90
PC300LC-7	207-25-61100	1532	1235	125	95	113	35-φ26	40-M24	90
PC300-8	207-25-61100	1532	1235	124	95	113	35	40	90
PC300-8	207-25-00121	1532	1235	124	95	113	35-φ26	40-M24*3	90
PC340	207-25-61200	1532	1235	124	95	113	35-φ26	40-M24*3	90
PC380LC-6K	207-25-61200	1532	1235	124	95	113	35-φ26	40-M24*3	90
PC400-7	208-25-61100	1563	1240	152	108	140	35-Φ29	40-M24	84
PC400LC-5	208-25-52100	1563	1238	152	108	140	35-Φ29	40-M24	84
PC400LC-5	208-25-52101	1563	1238	152	108	140	35-Φ29	40-M24	84
PC400LC-5	208-25-A2100	1563	1238	152	108	140	35-Φ29	40-M24	84
PC400LC-6	208-25-61100	1563	1238	152	108	140	35-Φ29	40-M24	84
PC400	208-25-61100	1563	1240	152	108	140	35-φ29	40-M24	84
PC450-7	208-25-61100	1563	1240	152	108	140	35-φ29	40-M24	84
PC600-7	21M-25-11100	1794	1380	190	138	160	35-Φ33	44-Φ29	100
pc600-7	21M-25-11102	1794	1380	190	138	160	35-Φ33	44-Φ29	100
PC600LC-6	21M-25-11100	1794	1380	190	138	160	35-Φ33	44-Φ29	92
PC600LC-8	21M-25-11101	1794	1380	190	138	160	35-Φ33	44-Φ29	100

PC800LC-8	209-25-00102	1980	1540	205	153	173	44	48	112
PC1250	21N-25-00201	2440	1955	238	168	200	56	60	132

DOOSAN SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total Height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
S140LC-V	109-00165	1202	945	84	75	70	36-Φ22	36-M20	80
DX225	109-00162	1327	1082	110	90	95	36	36	92
DX225	109-00162A	1327	1082	110	90	95	36-φ21	36-M20*1.5	92
DX225LC	109-00162	1327	1082	110	90	95	36-φ21	36-M20*1.5	92
DX225LCA	109-00162A	1327	1082	110	90	95	36-φ21	36-M20*1.5	92
DX225LCA	140109-00048A	1327	1082	110	90	95	36-φ21	36-M20*1.5	92
S225NLC	140109-00045	1327	1082	110	90	95	36-φ21	36-M20*1.5	92
SL220LC-V	109-00052	1328	1084	110	91	95	36-φ21	36-M20*1.5	92
225NLC-V	109-00052B	1328	1084	110	91	95	36-φ21	36-M20*1.5	92
225NLC-V	140109-00045	1328	1084	110	91	95	36-φ21	36-M20*1.5	92
255LC-V	109-00030B	1410	1131	117	89	105	35-φ25	36-M24*2	82
255LC-V	180-00297D3	1410	1131	117	89	105	35-φ25	36-M24*2	82
255lc-v	140109-00042	1410	1131	117	89	105	35-φ25	36-M24*2	82
255lc-v	140109-00043	1410	1131	117	89	105	35-φ25	36-M24*2	82
Dx300LCA	140109-00010A	1475	1165	120	90	110	35	36	85
S340	140109-00038	1544	1235	122	87	110	35-φ26	40-M24	90
S340LC-V	140109-00038	1544	1235	122	87	110	35-φ26	40-M24	90
S340LC-V	2109-1059a	1544	1235	122	87	110	35-φ26	40-M24	90
420	140109-00039	1549	1235	134	103	120	35-φ26	40-M24	90
S420LC-V	109-00161	1550	1235	135	102	120	35-φ26	40-M24	90
DX420LC	140109-00007A	1550	1236	132	103	120	35	40	90
470	109-00159	1682	1320	139	118	111	44	44	111

KATO SLEWING BEARING

No	Model	External diameter	Internal diameter	Total height	Outer ring height	Inner ring height	O.H Parameters	I.H Parameters	Tooth Number
1	250-7	811	584	84	67	67	30-φ17.5 e	30-φ17.5 e	75
2	307	811	584	84	67	67	30-φ17.5 e	30-φ17.5 e	75
3	HD450-5	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
4	HD450-7	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
5	HD512	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
6	HD513	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
7	HD516	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
8	HD400-7	1111	873	75	65	62	38-φ18 e	38-φ18.5 e	89
9	HD550	1163	961	94	66	84	36-φ18 e	36-M16*1.5 e	98
10	HD700-1	1310	1083	110	90	90	36-M20 e	36-M20 e	92
11	HD700-2	1310	1083	110	90	90	36-M20 e	36-M20 e	92
12	HD700-5	1300	1084	110	89	94	35-M20 e	36-M20 e	92
13	HD700-7	1320	1080	95	70	85	36-φ22 e	36-M20 e	92
14	HD820-1	1320	1080	95	70	85	36-φ22 e	36-M20 e	92
15	HD820-3	1320	1080	95	70	85	36-φ22 e	36-M20 e	92
16	HD820-7	1320	1080	95	70	85	36-φ22 e	36-M20 e	92
17	HD800-7	1402	1132	97	80	80	36-φ22 e	36-M20 e	96
18	HD900-7	1402	1132	97	80	80	36-φ22 e	36-M20 e	96

KOBELCO SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total Height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
SK75-8	YT40F00004F1	810	586	80	62	61	24	30	75
SK75 UR-3	2425U261F1	810	587	84	67	67	25	30	75
SK130LC IV	LP40FU0001F1	1093	880	85	60	75	28-φ17	36-M16	89
SK-140	YY40F00009F1	1131	921	85	60	75	34-φ17	36-M16	93
SK140SR	YY40F00009F1	1129	919.5	85	60	75	34	36	93
SK200	24100N7440F1	1312	1082	106	78	95	33-Φ22	36-M20	110
K907LC-2	24100N3978F	1312	1084	105	78	95	32-φ22	36-M20*1.5	110

SK200	YN40FU0001F1	1312	1082	106	?	?	33	36	110
SK200-6	YN40F00008F1	1312	1081.5	106	78	95	33-Φ22	36-M20	110
SK200-6	YN40F00004F2	1312	1082	105	78	95	33-Φ22	36-M20	110
SK200-8/ E215	YN40F00026F1	1310	1081	109	78	97	33	36	110
SK200-8	YN40F00026F2	1312	1082	106	78	95	33-φ22	36-M20*1.5	110
SK200-10	Yn40f00042f2	1310	1082	108	78	98	33-φ21.5	36-M20*1.5	110
SK210LC	YN40F00019F2	1312	1081.5	106	78	95	33-Φ22	36-M20*1.5	110
SK210LC-6	Yn40f00004f1	1312	1081.5	106	78	95	33-Φ22	36-M20*1.5	110
SK210LC-8	YN40F00026F1	1310	1081	109	78	97	33	36	110
SK220LC III/IV	24100N7441F1	1312	1082	106	78	95	33-Φ23	36-M20*1.5	110
SK230-6	LQ40F00004F1	1410	1131	120	88	110	33-φ22	36-M20*1.5	82
SK235	YN40F01004P1	1409	1080	116	88	106	33	36	110
SK250-6E	LQ40F00005F1	1416	1131	120	85	110	33-φ21	36-M20*1.5	82
SK250-8	LQ40F00014F1	1416	1131	120	85	110	33-φ21	36-M20*1.5	82
SK250LC-6E	LQ40f00004f1	1410	1131	120	88	110	33-φ22	36-M20	82
SK250NLC-6	24100N7441F1	1410	1131	120	88	110	33-φ22	36-M20*1.5	82
SK260-8	LQ40F000014F1	1418	1132	120	86	110	33-Φ21	36-M20*1.5	82
SK330	LC40F00019F1	1613	1272	120	100	110	35-φ26	36-M24*2	92
SK330-6E	LC40F00009F1	1564	1200	125	105	115	35-Φ26	36-M24	77
SK330LC V1	LC40FU0001F1	1564	1200	125	105	115	35-Φ26	36-M24	77
SK330LC-6E	LC40F00009F1	1564	1200	125	105	115	35-Φ26	36-M24	77
SK330-6E	LC40F00012F	1560	1200	125	105	115	35	36	77
SK350	LC40F00018F1	1613	1272	120	100	110	35-Φ26	36-M24*2	92
SK350ME	FG4E9648E-J6	1613	1272	120	100	110	35-φ26	36-M24*2	92

HITACHI SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total Height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
EX60-2	4193433	772	554.4	78	60	65	24-φ18	24-φ18	71
EX60WD -2	4193433	772	554.4	78	60	65	24-φ18	24-φ18	71
Ex60-5	43767553	781	554	76	60	63	24-Φ17	24-Φ17	71
EX100	9098995	1195	962	87	72	69	36-φ19	36-φ17	98
EX100-3	9102726	1092	862	84	68	70	36-Φ20	36-Φ18	88
EX150-5	9146953	1197	939	98	69	81	36	40	80
EX200	9098993	1312	1084	106	72	95	36-φ22	36-M20*1.5	92
ZX200LC-5G	9260971	1316	1082	96	76	85	37-φ21	36-M20*1.5	92
ZX200-3	9260971	1316	1082	96	76	85	37-φ21	36-M20*1.5	92
ZX200	9196732	1312	1082	106	72	95	32-Φ21	36-M20	92
ZX200-5G	9260971	1316	1082	96	76	85	37-φ21	36-M20*1.5	92
EX210-5	9102727	1310	1083	106	72	95	36-Φ22	36-M20	92
ZX210LCK	9169646	1312	1082	106	72	95	32-Φ21	36-M20*1.5	92
ZX220	9262248	1416	1137	110	84	97	36-Φ24	36-M22*1.5	83
EX220-1	9154037	1416	1137	110	84	97	36-Φ24	36-M22	83
ZX225US	9196732	1312	1082	106	72	95	32-Φ21	36-M20	92
ZX330-3LC	9260971	1312	1082	106	72	95	32/21	36-M20*1.5	92
EX270-5	9154037	1416	1137	110	84	97	36-Φ24	36-M22	83
ZX230	9154037	1416	1137	110	84	97	36-Φ24	36-M22*1.5	83
ZX230	9159646	1416	1137	110	84	97	36-Φ24	36-M22*1.5	83
ZX240	9196732	1416	1137	110	84	97	36-Φ24	36-M22*1.5	83
ZX240	9245728	1416	1137	110	84	97	35-φ24	36-M22*1.5	83
EX300-3	9112188	1531	1248	117	83	105	32-φ26	36-M24*2	91
ZX330LC-5G	9245698	1930	1297	121	95	110	36-φ29	36-M27*2	83
340 LCV	140109-00047	1543	1236	132	103	120	35-φ26	40-M24	90
ZX350-3	9245698	1629	1296	121	95	110	40-Φ29	36-M27*2	83
ZX370	9166468	1629	1296	121	95	110	40-Φ29	36-M27*2	83
ZX370	9169894	1629	1296	121	95	110	40-Φ29	36-M27*2	83
KH180-3	9099074	1630	1218	162	144	136	22-29	36-M27	88
EX400-5	9129521	1654	1275	129	117	110	36-Φ29	36-Φ29	107

ZX450	9129521	1652	1273	130	120	110	36-Φ29	36-Φ29	107
ZX650LCH	6016584	1754	1342	150	130	117	36	36	97
ZX800LD	9229741	1930	1495	160	148	135	40	40	108
ZX870-3	9321216	2040	1595	160	147	136	41-Φ35	48-Φ31.5	115
ZX870	6023643	2037	1595	160	148	136	41	48	115

LIEBHERR SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
R922	LE982706001	1215	940	115	72	105	48-φ22	56-M20	94
924HDSL	LE982751901	1215	940	115	72	105	48-Φ22	56-M20cloth	94
R924C	982751901	1215	940	115	72	105	48-Φ22	56-M20cloth	94
R924C	932833001	1215	940	115	72	105	48-Φ22	56-M20cloth	94
R924B	982751901	1215	940	115	72	105	48-Φ22	56-M20cloth	94
R934	933816501	1355	1012	125			40	48	92
R934HD-S	LE939500601	1355	1012	125	92	113	40-26through hole	48-M24	92
934	982752401	1355	1012	125	92	113	40-26through hole	48-M24	92
R-944C	933628601	1365	1008	150	112	140	60-Φ26	72-M24cloth	84
R944B	933626601	1365	1008	150	112	140	60	72	84

HYUNDAI SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
R140LC-7	81N4-01020	1196	963	90	79	80	36-φ19	36-M16*1.5	98
R210LC-3	81EM-00020	1202	945	84	75	70	36	36	80
R170W-7	81EM-00021	1202	947	83	75	70	36-φ22	36-M20*1.5	80
R200W-7	81EM-00021GG	1327	1083	110	89	94	30-φ22	36-M20	92
R210-7	81N6-00023BG	1327	1084	110	89	94	30-φ22	36-M20	92
R210LC-7	81N6-01020	1326	1084	110	89	94	30-φ22	36-M20	92
R210-7	81N6-00022	1326	1084	110	89	94	30-φ22	36-M20	92
R210-7	81N6-00021	1326	1084	110	89	94	30-φ22	36-M20	92
R210LC7	31N 812020	1326	1084	110	89	94	30-Φ22	36-M20	92
R210W-9S	81Q5-01020	1327	1083	110	89	94	30-φ22	36-M20	92
R210W-9S	81Q5-01021	1327	1083	110	89	94	30-φ22	36-M20	92
R220LC-9S	81Q6-00020	1326	1084	110	89	94	30-φ22	36-M20	92
R220LC-9S	81Q6-01020	1326	1084	110	89	94	30-φ22	36-M20	92
R220LC-9S	81Q6-01021	1326	1084	110	89	94	30-φ22	36-M20	92
R220LC-9S	81Q6-00021	1326	1084	110	89	94	30-φ22	36-M20	92
R250LC-7	81EN-00052	1410	1131	120	88	110	34-φ23	36-M20	82
290LC-7	81N8-0003	1526	1235	123	97	110	38-φ26	40-M24	90
R290	81N8-00021	1526	1235	122	87	110	37-Φ26	40-M24	90
R290	81N8-00022	1526	1235	122	87	110	37-Φ26	40-M24	90
R290LC 7A	4921797	1526	1235	123	97	110	38-φ26	40-M24	90
R290LC-7	81N8-00023	1526	1235	123	97	110	38-φ26	40-M24	90
R290LC-7A	81N8-00024GG	1526	1235	122	97	110	38-φ26	40-M24	90
R320-7	81N9-01020	1526	1235	122	97	110	38-Φ26	40-M24	90
R320LC-7	81N9-01021	1526	1235	122	97	110	38-Φ26	40-M24	90
R320LC-7	81N9-01022	1526	1235	122	97	110	38-Φ26	40-M24	90
R320LC-7	81N9-01022BG	1526	1235	122	97	110	38-Φ26	40-M24	90
R360LC-7	81NA-01020	1550	1250		108	140	35	40	106
R360LC-7	81NA-01022GG	1550	1250	152	108	140	35	40	106
R360LC-7A	81NA-01021BG	1550	1250	152	108	140	35	40	106

SUMITOMO SLEWING BEARING

No	Model	External diameter	Internal diameter	Total height	Outer ring height	Inner ring height	Outer ring hole	Inner ring hole	Tooth Number
1	SH50	615	451	53	40	43	20-φ13.5 e	20-φ13.5 e	92
2	SH60-1 21 hole	766	560	97	58	80	21-φ17 une	20-φ17 e	71
3	SH60-1 22 hole	765	562	97	56	80	22-φ17 une	20-φ17 e	71
4	SH120A1	1171	973	88	56	78	28-φ18.5 une	36-M16 e	98
5	SH120A2	1171	973	88	56	78	28-φ18.5 une	36-M16 e	98

6	SH120-1	1171	973	88	56	78	28-φ18.5 une	36-M16 e	98
7	SH120-2	1171	973	88	56	78	28-φ18.5 une	36-M16 e	98
8	120A3	1171	973	80	56	69	28-φ18.5 une	36-M16 e	98
9	120Z3	1171	973	87	65	78	28-φ18.5 une	36-M16 e	98
10	SH120C3	1171	973	87	65	78	28-φ18.5 une	36-M16 e	98
11	SH265	1169	973	85	55	75	28-φ18.5 une	36-M16 e	98
12	SH260	1169	973	85	55	75	28-φ18.5 une	36-M16 e	98
13	SH200A1	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
14	SH200A2	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
15	SH200A3	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
16	SH200C2	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
17	SH200C3	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
18	SH200Z3	1330	1093	102	74	92	31-φ22 une	36-M20 e	92
19	210-5	1330	1084	103	74	93	31-φ22 une	36-M20 e	92
20	210-A5	1330	1084	103	74	93	31-φ22 une	36-M20 e	92
21	SH220-3	1375	1094	121	80	111	26-φ26 une	36-M24 e	92
22	SH225	1329	1093	103	74	92.5	32-φ22 une	36-M20 e	92
23	SH240-3	1376	1092	123	88	114	27-φ26 une	36-M24 e	92
24	SH240-5	1377	1094	123	88	113	28-φ26 une	36-M24 e	92
25	SH280	1315	1083	99	65	88	32-φ22.5 une	36-M20 e	92
26	SH280	1330	1082	110	79	94	28-φ22 une	36-M20 e	92
27	SH350	1510	1193	135	100	125	38-φ26 une	43-M24 e	86

JCB SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
JCB 8060	234/11000	852	648.5	70	55	60	24	24	109
JCB JS130	332/K8067 （New）	1174	972	88	56	78	32-Φ18	36-M16	98
JCB JS130	JNB0146 （Old）	1174	972	80	56	70	28-Φ18	36-M16	98
JCB JS130	JNB0160	1174	972	80	56	70	28-Φ18	36-M16	98
JCB160	331/12091	1330	1093	102	74	92	31-Φ22.5	36-M20	92
JCB 205	333/P7280	1328	1092	102	74	92	31-φ22	36-M20	92
JS200LC	JRB0017	1328	1092	102	74	92	31-Φ22.5	36-M20	92
JCB JS220	JRB0017	1328	1092	102	74	92	31-Φ22.5	36-M20	92
JCB JS220	JRB0017	1328	1092	102	74	92	31-Φ22.5	36-M20	92
JCB 240	JBB0001	1375	1094	125	80	115	26	36	92
JCB JS240	916/10029	1375	1094	124	80	114	26-Φ26	36-M24	92
JCB JS330	JSB0022	1509	1192	135	100	125	38-φ26	43-M24	86
JCB 360	JSB0022	1510	1193	135	101	125	38-φ26	30-M22	86

VOLVO SLEWING BEARING

Model	Part Number	Outer Diameter	Inside Diameter	Total height	Outer Height	Inner Height	O.H Parameters	I.H Parameters	Number of Teeth
EC140B	VOE14520561	1196	963	90	79	80	36-Φ19	36-M16*1.5	98
EC210	SA1155-00061	1328	1080	110	90	90	33-Φ22	36-M20	92
EC210BLC	14563341	1327	1082	110	90	90	34-φ22	36-M20	92
EC210BLC	14563342	1327	1082	110	90	90	34-φ22	36-M20	92
EC210 2005	EC210V13948	1327	1080	110	90	90	34-Φ21.5	36-M20	92
EC210B	14563327	1328	1080	110	90	90	34-Φ21.5	36-M20	92
EC210B	14505766	1328	1080	110	90	90	34-φ22	36-M20	92
EC210BLC	14577178	1328	1080	110	90	90	34-φ22	36-M20	92
EC210BNC	14530323	1328	1080	110	90	90	34-φ22	36-M20	92
EC210LC	1155-00061	1328	1080	110	90	90	33-φ22	36-M20	92
EC210LC	14563328	1326	1083	108	90	90	34	36	92
EC240BLC	14563334	1462	1162	120	95	105	33	36	85
EC240BLC	SA1155-00040	1462	1162	120	95	105	33	36	85
EC240BNLC	14520572	1462	1162	120	95	105	33	36	85
EC290	14570794	1532	1235	123	90	113	35-Φ26	40-M24	90
EC290BLC	14563335	1533	1235	122	90	110	35-φ26	40-M24	90
EC290B	14563335	1532	1235	122	90	110	35-φ26	40-M24	90

EC290B	14520573	1532	1235	122	90	110	35-φ26	40-M24	90
EX300-3C	9112188	1531	1248	117	83	105	32-φ26	36-M24*2	91
EC360BLC	14563350	1550	1239	150	110	136	35	40	90
EC460BLC	14507709	1778	1393	120	110	110	40-Φ33	40-M30	112
EC480DL	14559204	1778	1393	120	110	110	40/33	40/M30	112
EC700BLC	14559205	1815	1375	205	148	180	48	60	100